



Obtén el mayor provecho que nuestros nuevos terminales POS ofrecen

Su implementación soporta distintos tipos de modelos y versiones



Entregarás a tus clientes tipos de pagos modernos, ágiles y sobre todo seguros



Guardia Vieja 255, Oficina 609,
Providencias, Santiago.

contacto@axonia.cl

+56 2 2210 8097 / +56 2 2210 8098
+56 9 6238 6422

H60-A Mobile Terminal

TPV inteligente con multiples métodos de cobro y gestión.



CPU	ARM Cortex-A7
Memory	128MB, Flash, 64MB SRAM Scalable
Display	2.8" colour LCD, 320 x 240 pixels ,electronic signature
Keypad	10 numeric & letter keys, 10 dedicated function keys
Magnetic Card Reader	Track1/2/3,Bi-directional
IC Card Reader	EMV Level 1 & 2 certified/ PBOC3.0
2 PSAM card	Extensible to 3pcs,ISO7816 certified
SIM card slot	1 SAM, Dual SIM
1 SD Card Slot	Standard Micro SD card to read and write
Contactless Card Reader	ISO / IEC 14443 Type A & B/Mifare, card status indicator
Printer	Super fast thermal printer ,30 lps, paper roll diameter: Φ40mm
Communicationt	Inbuilt GPRS, CDMA/ 3G(WCDMA\ EVDO)
Peripheral Ports	1XRS232,1XMicro USB
Voltage	Input: 110V~240V AC/50~60HZ/0.5, Output: 5V, 1A
Battery	7.4V/2200mAH Li-ion battery
Environment	Operating Temperature: 0%~50% . Storage Temperature: -20%~70%.
Certification	Relative Humidity:5%~95%(non-condensing) PBOC L1&L2、QPBOC L1&L2、EMV L1&L2、PCI PTS5.X



M60-C Mobile Terminal

TPV inteligente con múltiples métodos de cobro y gestión.



Processor	32-bits High-performance security processor
Memory	512KB flash, 64KB SRAM, External : 2MB flash
Display	2 inches 320*240 Color LCD display
Keypad	10 alphanumeric keys, 4 function keys, 1 power key
Magnetic Card Reader	Compliant with ISO7811, ISO7812. Track 1/2/3, Bi-directional Swipe
IC Card Reader	Meets EMV/PBOC 3.0 standards
Contactless Reader	Supports ISO /IEC 14443 Type A & B, Mifare Standards
Status Bar	4 signal lights
Comm type	Bluetooth 4.0, Support Android, iOS and Windows
Interface	Micro USB
Language	Support Chinese, English, etc.
Battery	Rechargeable lithium battery, 3.7V/250mAh
Working Env	Temperature: 0~ 50°C(32 ~ 122°F). Humidity: 10% ~ 90% (non-condense)
Storage Env	Temperature: -20 ~ 70°C(-4 ~ 158°F). Humidity: 5% ~ 95% (non-condense)
Cable	USB Cable
Dimensions	120mm*65mm*17.5mm(L*W*H)
Weight	116g(include battery)
Certification	PCI PTS 5.x, EMV L1/L2, PBOC 3.0 L1/L2





WCT-S8 Mobile Terminal

TPV inteligente con multiples métodos de cobro y gestión.



Processor	4 core ARM Cortex-A53
Memory	1GB RAM + 8GB Flash
OS	Android 7.0 Security Payment OS
Contactless Card Reader	NFC 13.56 MHz, Support ISO/IEC 14443 Type A&B, Mifare
Smart Card Reader	EMV & PBOC Compliant
Magnetic Card Reader	Triple-track bi-directional, ISO 7810 Compliant
Certification	EMV L1/ L2, PBOC L1/ L2, PCI PTS 5.1
Thermal Graphic Printer	Paper Width 58mm, 40mm, 85mm/s
Biometric Module	Capacitive Fingerprint Module, FBI Certificated (Optional)
Display	5.5" (1280*720) capacitive color touch screen; signature capture, video capable
Communication	4G: TD-LTE/ FDD-LTE 3G: TD-SCDMA/ WCDMA/ CDMA2000 2G: EDGE/ GPRS
GNSS	Support
Security Features	DES, TDES, AES, RSA, ECDSA
Keypad	Virtual Keypad
Audio	Digital Audio Speaker, Microphone
Dimensions	120mm*65mm*17.5mm(L*W*H)
Card Slots	4 PSAM Slots, 2 SIM Slots
Bluetooth	4.1 LE, 2.4GHz ISM 2402MHz~2480MHz
WiFi	802.11b/g/n WLAN
USB	Micro USB, Support OTC, Data Transfer, Recharging
Camera	5Mega, CMOS, AF, JPEG picture, Video Support Bar code and QR code
Battery	Rechargeable, 3.7V, 5800mAh
Dimensions Weight	203mm*85mm*53mm, 480g(With Battery)



Guardia Vieja 255, Oficina 609,
Providencias, Santiago.

contacto@axonia.cl

+56 2 2210 8097 / +56 2 2210 8098
+56 9 6238 6422




WCT-MINI Mobile Terminal

TPV inteligente con múltiples métodos de cobro y gestión.



Operation System	Security OS, Android 5.1
CPU	Qualcomm Quad-core, 1.1 GHz
Memory	1GB DDR3, 8GB Flash Optional: 2+16
Display	4.5 inch, Resolution: 854*480
Screen	High Sensitivity Capacitive Touch Screen
Camera	Rear Camera: 5 MegaPixel Auto Focus Support Optional: 0.3m. FF; Support 1D/2D Code
Communication	2G:GSM/EDGE 850/900/1800/1900 - 3G:WCDMA Band 1/2/5/8 - 4G: FDD Band 1/,/7; TDD Band: 38/39/40/41
WIFI	Support 2.4G/5G, a/b/g/n
Bluetooth	BT 4.0+BLE
GPS	Support: GPS/A-GPS, GLONASS, BEIDOU
NFC	ISO/IEC 14443 Type A&B, Felica, Mifare
IC Card Reader	ISO/IEC 7816, Conform to EMV L1/L2
Certifications	PCI PTS, EMV L1&L2, EMV Contactless L1, Visa Paywave, MasterCard Paypass, MasterCard TQM, CE, Conformity Certificate of Explosion-Proof
Magnetic Card Reader	ISO/IEC 7816, Track 1/2/3, Bi-directional
PSAM	1 PSAM Slots, ISO/IEC 7816
Indicator	4 Independent POS indicators
Buzzer	Support
Memory Extension	Micro SD/TF, 64GB
USB Port	Micro USB, OTG Supported
SIM Card Slot	1 Slot, 25*15mm
Audio	1 Speaker, 1 Microphone
Auxiliary Lamp	Support Read Light Position, Withe Light Compensation
Keys	Power Key, Push-talk Key, Volume Key, Multifunction Key (Deault Scanning Key); Touch Key: MENU/HOME/BACK Keys
Battery	3000mAh
Power	Input: 100-240V, 50/60Hz 0.35A
Dimensions	136*69*22.1 mm
Accessories	Adaptor, USB Cable
Optional Accessories	BT Earphone, BT Printer, Waist Pocket



Guardia Vieja 255, Oficina 609,
Providencias, Santiago.
contacto@axonia.cl
+56 2 2210 8097 / +56 2 2210 8098
+56 9 6238 6422